

Plum Creek MarineDeck™	
SPECS	<ul style="list-style-type: none"> • Designed for rigorous marine use with superior “CP” grade face • All Group 1, Struc 1 Species • Available with solid core under the face • 2 side panels available
FACES	<ul style="list-style-type: none"> • “C” plugged grade veneer • Quality wood plugs or putty repairs, minimal use of polyurethane patch • Splits over 1/16” are filled. Sound, tight knots up to 1 1/2" • Face is touch sanded with 60 grit paper
BACKS, CENTERS & CORES	<ul style="list-style-type: none"> • Plum Creek’s High Integrity Ultra-Core™ construction features composed cross bands for tight core gap tolerance more stringent than APA and industry specs • One piece “C” grade or better center and back
CONSTRUCTION & THICKNESS	<p>Thickness Ply count</p> <p>1/4" 3 Ply</p> <p>3/8" 4 Ply</p> <p>1/2" 5 Ply</p> <p>5/8" 5 or 7 Ply</p> <p>3/4" 7 Ply</p> <ul style="list-style-type: none"> • Standard size 4’ x 8’ • Panel thickness to 1 1/2" • Solid long length to 102" • Scarfed length to 16' • Tongue and groove available on 5/8" - 1 1/8" • Underlayment stamp available